



Made in the U.S.A.

KING-HUGHES FASTENERS CORPORATION

550 Fourth Street
P.O. Box 98
Imlay City, MI 48444
Phone: 810-721-0300
800-779-3762
Fax: 810-721-0400

SUBJECT: SPECIFICATIONS OF HOG RING FASTENERS

DIMENSIONAL

Open:	1-1/2 inches (3.81cm)
Closed:	9/16 – 5/8 inches (1.43 – 1.59cm)
Wire Diameter:	0.120 inch (3.05cm) [11 gauge]
Packaging:	1,600 pieces per box, 40 pieces per strip, and 96 boxes per pallet
Weight per box:	16lbs. (7.3 Kilograms)

MATERIAL SPECIFICATION

11G40	The galvanized rings shall conform at ASTM A 641-92 for zinc coatings; ASTM A764-95 for chemical and mechanical specifications; and ASTM E 8/MPT 2004 for tensile strength requirements.
11SS40	Shall conform to ASTM A 313 type 302, Class I; and ASTM E 8/MPT 2004 for tensile strength requirements.
11AL40	Shall conform to ASTM B 341, and shall have a minimum weight of aluminum coating of .32oz/sq.ft.

TOOL INTERCHANGABILITY

- C1511 King Hughes
- SC-50 Spenax
- SC-50HP Spenax